

Rental Equipment

SKYTRAK 8042



JLG SkyTrak 8042 Telehandler Max Lift Weight 8000 Lb. and Height 41' 11in

8000 lb / 3628.74 kg maximum lift capacity

41 ft 11 in. / 12.78 m maximum lift height

26 ft. maximum reach

New, intuitive single joystick controls all boom functions

Maximize productivity with improved boom speeds

BANDIT SG 40 STUMP GRINDER



- Rubber track undercarriage
- 3-position operator's console
- Electric switch for cutter wheel engagement
-

WEIGHT: 1,500 LBS

CUT DEPTH: 12"

CUT WIDTH: 34.5"

HORSEPOWER: 38 HP

FUEL: Gas

DRIVE: Self Propelled

BOBCAT MT100

No need for wheelbarrows, shovels or other hand tools when you roll onto jobsites with the Bobcat® MT100 mini track loader.

Fit through gates, doorways and other narrow spaces

1,000 lb. rated operating capacity

Powerful breakout force and impressive lift height

Tackle residential and light commercial tasks like grading, trenching, patio prep, moving gravel or mulch w/ the Bobcat mt100 rental. This 1,000 lb mini skid steer features a walk-behind design, 42" low-profile bucket & hydrostatic drive for power & precision.



BOBCAT E-10 MINI EXCAVATOR

The Bobcat E10 is a compact and highly maneuverable mini excavator designed for tight-space digging. With an operating weight of 2,593 lbs (1,176 kg) and a maximum dig depth of 6 feet (1,828 mm), it is perfect for small construction projects, landscaping, and utility work. Its zero tail swing design allows operators to work in confined areas without worrying about damage to surroundings.



Key Features

- Ultra-Compact Size - Easily fits through gates, doorways, and narrow work areas.
- Zero Tail Swing - Work close to walls and obstacles without risk of collision.
- Retractable Tracks - Adjusts from 28 inches (711 mm) to 43 inches (1,092 mm) for maximum stability.
- Fuel-Efficient Diesel Engine - Delivers reliable performance with low fuel consumption.
- Simple and Intuitive Controls - Designed for smooth operation, even for first-time users.
-

Best For

- Indoor and tight-space excavation
- Landscaping and trenching
- Residential and utility work

BOBCAT E-35 MINI EXCAVATOR

The Bobcat E35i compact excavator is a mid-sized machine offering a balance of power, performance, and maneuverability. With a 10 ft 2 in (3,104 mm) max dig depth and an operating weight of 7,699 lbs (3,493 kg), it provides excellent stability and reach. The zero tail swing design allows efficient operation in confined spaces without the risk of rear overhang collisions.

Key Features

- Zero Tail Swing - Work close to walls and obstacles without rear overhang.
- Powerful 24.8 HP Diesel Engine - Delivers reliable and fuel-efficient performance.
- Advanced Hydraulics - Ensures smooth, precise control for efficient digging.
- Spacious Operator Cab - Designed for comfort with ergonomic controls and excellent visibility.
- Attachment Versatility - Compatible with a variety of tools for digging, grading, and material handling.
-

Best For

- Residential and commercial excavation
- Landscaping and site preparation
- Utility work and trenching



BOBCAT T64

- DIMENSIONS- L= 107"/134.9" w Bucket ... W= 67"/68" w Bucket ... H= 80.5"
- WEIGHT- 8,727 lbs.
- LIFT CAPACITY- 2,300 lbs.
- TRACKS- Rubber L= 54.3" On Ground / W= 12.6"
- DUMP HEIGHT- 120" @ Hinge Pin
- REACH- 36.7" @ Max. Height
- TRAVEL SPEED- 7.2-10.2 MPH
- TURN RADIUS- 81.5"
- ENGINE- 68HP Turbo Diesel (TIER 4)
- FUEL CAPACITY- 28.3 Gallons
- GROUND PRESSURE- 5.7 PSI
- HYDRAULIC FLOW- 17.6 GPM Aux STD Flow

What can you do with a Bobcat T64 Compact Track Loader (Rubber Track Skid Steer) rental?

- Backfill trenches
- Prepare grounds for landscaping
- Snow removal
- Remove debris from construction sites
- Sod removal
- Clear land and load rubbish into bins
- Plant trees
- Remove stumps
- Load pickup trucks, hoppers and spreaders
- Grade and level driveways
- Load sand and gravel

GENIE 5519 TELEHANDLER

- 5,500 lb. Capacity
- 19 ft. Lift Height
- 11 ft. Forward Reach
- 4,400 lbs. Capacity at Max. Height
- 1,900 lbs. Capacity at Max. Reach

• The highly maneuverable Genie GTH-5519 telehandler – often the first machine to arrive at a new job site and the last to leave.

• The GTH-5519 works hard in tight spaces to unload trucks, carry tools and perform site cleanup.



GENIE S-40 BOOM LIFT



Genie® telescopic S™-booms offer greater horizontal outreach than any other type of aerial platform — perfect for areas with limited access in construction and industrial applications.

- 45 ft. 6 in. Working Height
- 28 ft. 11 in. – 31 ft. 1in. Maximum Horizontal Reach
- 500 Lbs.
- 8 ft. 2 in. Machine Width
- 26 ft. 4 in. Machine Length

GENIE GS 1930 / JLG 1932

If your next job or project requires unobstructed vertical access, rent a scissor lift. Scissor lift rentals provide an elevated indoor or outdoor platform for painting as well as sprinkler system, electrical or HVAC repair and installation.

This scissor lift can be used for indoor electrical maintenance and installation, indoor sprinkler system maintenance and installation, facility maintenance, HVAC, and painting.

Requires a firm, level surface. Non Marking tires can not be used on gravel or over debris.

- Front-wheel drive and zero inside turning radius
- Easily pass through standard single or double doors
- Large platform workspace with 36 in (0.91 m) roll-out platform extension

Width: 2' 6"

Weight: approximately 3,200 lbs

Platform Height: 19' (25' working height)



GENIE 2632



The Genie GS-2632 E-Drive self-propelled electric scissor lift is ideal for maneuvering in tight spaces, making it the right choice for indoor and outdoor construction, maintenance and installation applications with firm, level surfaces.

- 32 ft. Working Height
- 500 lbs. Capacity
- 32 in. Machine Width
- 89 in. Machine Length
- 4,413 lbs. Machine Weight

HAULOTTE 45' TOWABLE ARTICULATING BOOM LIFT



Haulotte 4527 A 5Ft. Electric Articulating Towable Boom Lift can be towed by a standard half-ton pickup truck - No commercial driver's license needed. Superior combination of industry leading capacity and outreach. Hydraulic outriggers and automatic leveling allow operation in under 30 seconds. Air / water lines and 110V GFI protected power to the platform.

Working height = 51 ft.

Platform height = 45 ft.

Lift capacity = 500 lb.

2" Ball

HAULOTTE 55' TOWABLE ARTICULATING BOOM LIFT



Haulotte 5533 A 55 Ft Electric Articulating Towable Boom Lift can be towed by a standard half-ton pickup truck - No commercial driver's license needed. Superior combination of industry leading capacity and outreach. Hydraulic outriggers and automatic leveling allow operation in under 30 seconds.

Air / water lines and 110V GFI protected power to the platform.

Working height= 61 ft 3 in.

Platform height=55 ft 3 in.

Lift capacity=500 lb

HONDA GENERATOR EU2000I



2200 watt 120V inverter generator with CO-MINDER™

- Ideal for TV, DVD, satellite, fridge, coffee pot, & more
- Super quiet & lightweight
- Inverter - stable power
- CO-MINDER: advanced carbon monoxide detection system

HUSQVARNA CORE DRILL



DMS 240 is an electric drill motor and stand system for a wide variety of core drilling applications. An ideal system for medium core drilling in walls, floors and roofs up to 10 in. diameter. The stand is easy to tilt, and the back support provides reliable and stable angle drilling, saving you setup time and body stress. This system can be used for ventilation, plumbing waste evacuation pipes, barriers and road signs.

HUSQVARNA K770 CONCRETE CUT OFF SAW



This dependable cut-off saw works great for various cutting applications in construction and landscaping. Various blades available for concrete, asphalt or a mix use blade.

Power - 5 hp

Max Depth of Cut - 5 in

Blade Capacity - 14 in

Arbor - 1 in

HUSQVARNA SOFT CUT SAW

The Husqvarna Soff-Cut 150 saw is designed for residential and light commercial applications. The lightest gas saw in the Soff-Cut range, the 150 is designed for ease of use and convenience. Features include a patented low noise blade enclosure which allows the unit to be used in residential areas with minimal disruption. In addition, the low-dust blade block system allows the saw to cut dry, and it controls the debris for easy cleanup.

Cutting depth, max 1.5 in



HYSTER 50 FORKLIFT

The H 50 fork trucks are built strong to handle the toughest applications. This warehouse forklift can handle stock, pallets and other loads easily.



- Tires: Pneumatic
- Rated Capacity: 5,000 lbs
- Load Center: 24 in
- Overhead Guard Height: 85 in
- Overall Width, Standard Tread: 45.6 in
- Length to Face of Forks: 100.7 in
- Truck Weight: 8,399 lbs
- Highlights: 3-stage mast, side-shift and forks
- Max fork height: 10.9ft
- overall width: 3.8ft
- turning radius: 7.1ft
- wheelbase: 5.4ft

HYSTER 80 FORKLIFT

Lift stock, pallets and other loads easily and securely with this warehouse forklift. This heavy-duty, durable lift truck has a maximum capacity of 8,000 lbs. It has a two-stage mast for high visibility and efficient lifting speed at full load.



8,000 lb capacity with a 24-inch load center, featuring pneumatic tires, and solid dimensions like a roughly 7-8 ft lowered mast height and around 9-10 ft max fork height, built for high-intensity indoor/outdoor work with good gradeability (around 30%)

Unit Weight: Approximately 13,000 to 13,500 lbs

JLG 450 AJ ARTICULATING BOOM LIFT

The JLG 450AJ is a 45-foot articulating boom lift with a 25-foot horizontal outreach, 550 lb unrestricted platform capacity



Performance & Dimensions

- Platform Height: 45 ft (13.72 m)
- Horizontal Outreach: 25 ft (7.62 m)
- Platform Capacity: 550 lbs (unrestricted) / 1000 lbs (HC3)
- Working Height: Approx. 51 ft
- Up & Over Height: 24 ft (7.32 m)
- Swing: 355 degrees (non-continuous)
- Jib Articulation: 144 degrees
- Turning Radius: Around 15 ft 8 in (outside)
- Machine Weight: : approximately 14,150 lbs

JOHN DEERE 2025 TRACTOR

John Deere 2025R 4 wheel drive with loader bucket and backhoe attachment.



Ideal for loader work, and property maintenance/landscaping.

- 23.9 HP diesel Engine
- 4 wheel drive with hydrostatic drive
- Power steering
- John Deere 120R front loader with 54" bucket, 72" lift height, 533 lb. cap.
- John Deere 260B backhoe with 74" digging depth, 12" bucket

MUDMIXER

1 yard per hour output -- "Pour concrete as fast as you can load the hopper"

45 80lb bags/hr through the machine with no equipment failures

Works anywhere trucks can't reach -- basements, tight spaces, second floors

Waterproof solenoid & upgraded electrical -- reliable performance in any job site or weather condition

Reinforced steel chute with precision flow control -- handles rocks without damage

Stainless steel fittings & 3-position locking -- built for daily commercial use

2-year warranty -- double the industry standard

Works with concrete, mortar, stucco mix, poolkrete, and specialty mixes

Winner of Concrete Contractor Top Products Award

Winner of Equipment Today Contractors' Top 50 New Products Award

As Seen on Fox News, Lowes & Home Depot



NORTH STAR 3" TRASH PUMP

- Multidirectional discharge moves fluids where you want them
- Strong 23ft. max. suction lift
- FCD45 cast iron impeller and volute last longer for semi-trash operations
- Silicon carbide seals are 2x harder, 15% tougher and 50% stronger than common aluminum oxide seals

50' sections of discharge hoses available

10' Suction hose



MUDMIXER

1 yard per hour output -- "Pour concrete as fast as you can load the hopper"

45 80lb bags/hr through the machine with no equipment failures

Works anywhere trucks can't reach -- basements, tight spaces, second floors

Waterproof solenoid & upgraded electrical -- reliable performance in any job site or weather condition

Reinforced steel chute with precision flow control -- handles rocks without damage

Stainless steel fittings & 3-position locking -- built for daily commercial use

2-year warranty -- double the industry standard

Works with concrete, mortar, stucco mix, poolkrete, and specialty mixes

Winner of Concrete Contractor Top Products Award

Winner of Equipment Today Contractors' Top 50 New Products Award

As Seen on Fox News, Lowes & Home Depot



NORTHSTAR GENERATOR 8000



- Auto-idle control
-
- Four 120V, 20 Amp outlets with GFCI
-
- One 120V, 50 Amp outlet
-
- One 120V, 30 Amp locking plug outlet
-
- One 120/240V, 30 Amp locking plug outlet

NORTHSTAR PLATE COMPACTOR



- 3,968 lbs. of compacting force
- 65-82 feet per minute travel speed
- 21-1/2in. x 16-5/16in. compacting plate
- 6,400 vibrations per minute
- 163cc Honda GX160 OHV engine with cast iron cylinder liner

HILTI TE-3000-AVR ELECTRIC JACKHAMMER



Exceptionally powerful breaker for heavy-duty concrete demolition, asphalt cutting, earthwork and driving ground rods

- Working direction: Floor
- Tool chuck type: TE-H (Hilti HEX 28)
- Weight according EPTA-Procedure 01/2003 without battery: 59.7 lb

JLG SKYTRAK 6036

SkyTrak telehandlers are hard-working machines for hard-working people. Redesigned to enhance comfort and productivity, these machines deliver what you need, when you need it. They offer the maneuverability and stability to handle the toughest terrain.

Rated Capacity - 6,000 lb

Maximum Lift Height - 36 ft 1 in.

Load at Max Height - 6,000 lb

Maximum Forward Reach - 22 ft 4 in.

Load at Max Reach - 1,800 lb

Frame Leveling - 10°

Lift Speed (boom retracted) - Up / Down - 11.5 sec / Down 9

Boom Speed - Extended / Retracted - 13.5 sec / 14 sec

Top Travel Speed (4-Speed) - 19 mph

Drawbar Pull (loaded) - 22,000 lb

Outside Turning Radius - 165 in.

Operating Weight - 21,300 lb

Gross Power Basic - 74 hp

Maximum Torque @ 1400 rpm - 340 lb-ft

Fuel Tank Capacity - 35 gal

